

UFC SERIES PwrKart™ 400Hz GROUND POWER UNIT 60kVA to 90kVA



MOBILE CONFIGURATION
(Shown with standard touch screen panel)

STANDARD FEATURES:

- IP55
- Certified to UL 1012
- 3 Phase, 380-480VAC Input
- Indoor/Outdoor (Hangar/Ramp) Use
- ≤ 5% Input Current Distortion at max load
- Automatic Input Line Monitoring
- Advanced Integrated Display (AID™) Console
- 8000 Event Log / Diagnostics
- TCP/IP/Ethernet interface (Modbus)
- Internal Communication Ports - USB, RJ45 (ETHERNET), RS485 (Modbus), & RS232
- External Communication Port – USB
- 15% Automatic Line Drop Compensation
- Emergency Power “OFF” Switch
- 18-Inch Hazard Area Clearance
- No Break Power Transfer (NBPT) Compatible
- I/O Voltage, Current, & Frequency Monitoring
- Elapsed Time Meter
- Sleep Mode
- Front Panel Voltage Adjust
- Front Panel Summary Fault Indicators
- Input & Output Cable Racks
- Input High Voltage Transient Protection
- Multi Language Display - Arabic, Asian, English, French, German, Italian, Portuguese, Russian and Spanish, Others - Specify

MECHANICAL SPECIFICATIONS:

Size: See Figure 1
 Weight: 60.0kVA = 753lbs. (342kg.)
 75.0kVA = 925lbs. (420kg.)
 90.0kVA = 1,017lbs. (461kg.)
 Enclosure: NEMA 250 - Type 3SX
 Cooling: Forced Convection

APPLICATION:

Since its beginning in 1960, Unitron has specialized in the design and development of reliable solid-state power systems. Through an innovative design, advanced self-diagnostic systems (BITE) and modular construction, Unitron products assure maximum power availability and minimal repair time.

The PwrKart Series includes lightweight 115/200VAC, 400Hz, 28VDC, and 270VDC mobile converters for aircraft ground power applications in the hangar or ramp area. With one of the lightest weight-to-power rating ratio in the market, all Unitron mobile units are easily maneuvered by a single person within the hangar environment. This eliminates the need for expensive towing equipment or additional labor that other Ground Power Units (GPUs) may require.

Output power ratings for the 115/200VAC, **400Hz mobile PwrKart** range from 20kVA to 90kVA. Larger power ratings are available in towable, fixed and bridge-mounted configurations. In addition, Unitron offers a combination AC/DC GPU, which provides simultaneous 115/200VAC, 400Hz or 270VDC at 72kW, with 28VDC power from a single unit.

OPTIONS:

- Alternate input voltage range 3 Phase, 208-240 or 600VAC input
- Various Convenience Outlets (Specify Voltage and Frequency)
- 50 or 100 Foot Input Power Cable (Pigtail, Specify Required Length)
- AC Output Power Cable with Plug (Specify Required Length - Available in 30 or 60 foot standard lengths)
- Output Universal Aircraft Safety Interlock Circuit Disconnect (Single or Dual)
- External Communication Port - Ethernet
- Output Safety Disconnect
- 300% overload for 6 seconds or 425% overload for 1 second* (Specify)
- 28VDC or 270VDC Output
- Alternate Mounting Configurations Available
- Pneumatic Ramp Tires
- Custom Paint & Decals (Standard Color - White)
- Bench Top Voltage Adjust
- Ground Fault Monitor
- CSA Certified
- CE Mark Certified
- Lockable Front Door
- Neutral Interrupt Protection
- Universal Safety Interlock

*IAW MIL-STD-704F and ISO 6858: 2017

SPECIFICATIONS / STANDARDS (Meets or Exceeds):

NFPA 70 (NEC 500)	SAE ARP 5015
EN 60079-10	MIL-STD-1472
DFS-400	MIL-STD-704F
ISO 461-1/2	UFGS 26 35 43
ISO 1540	EN 61000-6-2 and -4**
ISO 6858	2006/95/EC**

*Defined Basis of CE Mark Certification



This product was manufactured in a plant whose quality management system is registered to ISO 9001:2015.

GENERAL SPECIFICATIONS

INPUT:

Input Current Distortion	≤ 5%, typically 3%
Voltage	380 - 480 volts, +10%, -15%, 3Ø, 3 or 4 wire plus ground (Alternate Voltages Available)
Frequency	50 - 60 Hz ± 10%
Phase Rotation	Any
Protection	Over/undervoltage, loss of phase, overcurrent, short circuit. Voltage transient protection IAW IEEE C62.41.1, Location Cat. B/C
Inrush Current	No greater than 100% of full load current

ENVIRONMENTAL:

Acoustical Noise	< 65 dBA maximum at 5 feet (1.5m)
Temperature Range	-40°C to +55°C
Relative Humidity	10 - 95%, Non-Condensing
Ingress of Water	Type 3SX, IP55

ENERGY FACTORS:


Efficiency	94% typical at full load; 92% typical at half load; varies depending on configuration
Energy Efficiency Ratio	20.0 typical

OUTPUT:

Power Rating	60, 75, or 90 kVA (Specify)
Overload:	100% continuous; 110% for 60 min; 125% for 10 min; 150% for 2 min; 200% for 20 sec
Voltage*	115/200 volts, 3Ø, 4 wire, grounded neutral
Voltage Adjust*	± 15%
Crest Factor	1.414 ± 3%
Voltage Regulation	± 1.0% under all conditions of line, balanced loads and temperature
Voltage Transients	IAW MIL-STD-704F
Frequency Regulation	400 Hz ± 0.01% under all conditions of line, load and temperature
Frequency Transients	None
Phase Angle Regulation	± 1° for balanced loads; ± 2° for unbalanced loads
Harmonic Distortion	2.0% maximum
Protection	Overload, short circuit, over/undervoltage and safety disconnect
Automatic Line Drop Compensation (ALDC)	15%

*Also available 120/208 VAC, adjustable ±10%

FIGURE 1



**UFC SERIES PwrKart™
MOBILE GROUND POWER UNIT (GPU)**